

Preliminary Data Sheet

198mm x 82mm x 21mm Label 195mm x 80mm x 20mm

Bulk Outline

Packge	Quantity per box		
DO-41	250 x 4 Divisions		
DO-15	125 x 4 Divisions		
DO-201AD	50 x 4 Divisions		

Ordering Information

Packge Type	STD/FR	SKY	UF/HER	Device Suffix
DO-41	1,000pcs	1,000pcs	1,000pcs	No suffix
DO-15	500pcs	500pcs	500pcs	No suffix
DO-201AD	200pcs	200pcs	200pcs	No suffix

Number: DB- 213 March 2010 / A



Preliminary Data Sheet


Axial-Lead Tape Packaging Standards

This axial-lead component's packaging requirements use in automatic testing and assembly equipment. And this standard practices for lead-tape packaging of axial-lead components meets the requirements of EIA Standard RS-296-D "Lead-taping of Components on Axial Lead Configuration for Automatic Insertion".

52mm Intermediate Box : 252mm x 75mm x 80mm

26mm Intermediate Box: 250mm x 50mm x 98mm






Ordering Information

Packge Type		Quantity Per Box			
		STD/FR	SKY	UF/HER	Device Suffix
DO-41	52mm	2,500pcs	2,500pcs	2,500pcs	ТВ
DO-41	26mm	3,000pcs	3,000pcs	3,000pcs	T26B
DO-15	52mm	1,500pcs	1,500pcs	1,500pcs	ТВ
DO-201AD	52mm	500pcs	500pcs	500pcs	ТВ

Taping Dimensions



Package	DO-41		DO-15	DO-201AD
Description	Millimeters		Millimeters	Millimeters
Standard Width	52	26	52	52
Tape Spacing (B)	52.0 ~ 52.8	26.0~26.4	52.0 ~ 52.8	52.0 ~ 52.8
Component Pitch (C)	5.0 ± 0.4	5.0 ± 0.4	5.0 ± 0.4	10.0 ± 0.4
Untaped Lead (L1 – L2)	± 1.0	± 1.0	± 1.0	± 1.0
Body Offset (F)	± 1.0	± 1.0	± 1.0	± 1.0
Bent (D)	1.2 Max	1.2 Max	1.2 Max	1.2 Max
Tape Width (G)	6.0 ± 1.0	6.0 ± 1.0	6.0 ± 1.0	6.0 ± 1.0
Tape Mismatch (E)	1.0 Max	1.0 Max	1.0 Max	1.0 Max
Lead Beyond Tape (H)	0	0	0	0

Number: DB- 213 March 2010 / A



NOTICE

The information presented in this document is for reference only. Tak Cheong reserves the right to make changes without notice for the specification of the products displayed herein.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Tak Cheong Semiconductor Co., Ltd., or anyone on its behalf, assumes no responsibility or liability for any damagers resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website http://www.takcheong.com, or consult your nearest Tak Cheong's sales office for further assistance.

Number: DB-111 April 29, 2008 / A